

REV.	LOCAS.	DESCRIPTION	DATE	DRAWN
01		INITIAL RELEASE.	2012.05.17	尹 晖

Specifications





Current Rating: 2Amp
Insulation Resistance: 1000M Min.
Dielectric Withstanding: 500V AC
Contact Resistance: 20m Max.
Operating Temperature:-65°C to +105°C

Materials

Contact Material: Phosphor Bronze

Insulator Material: Nylon 6T UL94V-0,

All materials must be ROHS materials



Recommended P.C.B. Layout
Tolerance:±0.05mm

Ordering Information

FFD113 - XX XX A 01

No. of Pins per Row Contact Plating
02~40
01=Tin
02=Gold Flash
Duplex plating
05=Gold Flash /Tin
...

深圳市硕康达科技有限公司 ShenZhenShi Sokcom Technology Co., Ltd					GENERAL TOLERANCE			DESIGN: 尹 晖	DATE: 2012.05.17	DWG. NO.	TITLE. 2.00 FEMALE HEADER SINGLE ROWS DIP TYPE
					X. ± 5.0"	X. ± 0.30	CHECKED:	DATE:	FFD113-A01		
					.X" ± 3.0"	.X ± 0.25	AUDITED:	DATE:	PART NO.		
					.XX ± 2.0"	.XX ± 0.15	APPROVED:	DATE:	FFD113-XX XX A01		
REV.	01	UNIT. mm	SCALE. 1:1	PAGE. 1/1							